

1/8" - 1/16" SPECIAL ADAPTERS



USES :

TOP INDUSTRIE 1/8"- 1/16" special adapters work for pressures up to 2000 bar. They are highly reliable, and renowned for their excellent sealing. TOP INDUSTRIE fittings set the standards in high pressure industry.

FEATURES :

- Works for pressures between 0 and 2000 bar.
- Works with both liquids and gases.
- Material : 1.4404 (316L)
- HP Tubing : 1/8" or 1/16"
- Maximum Temperature : 200°C
- Compressed ferrule type HP connection.

- Leak detection holes.

- All our fittings are equipped with ferrules and gland nuts.

OTHER OPTIONS :

- Other materials : B2, C 276, titanium, etc.
- Mounting holes.

TYPE	A HP TUBE		B CONNECTOR	REFERENCE	• CONNECTOR TO GAS CYLINDER 	PRESSURE	A HP TUBE		REFERENCE	• NON MACHINED 		
	inch	mm					bar / psi	inch			mm	
HYDROGENE	1/8"	3,2	A-L	920 58 00	• SPECIAL NIPPLE ADAPTOR 	1000 14500	1/8"	3,2	920 16 00	• SPECIAL ADAPTOR RUSKA 		
OTHER GASES	1/8"	3,2	A-L	920 59 00		1000 - 2000 14500 - 29000	1/16"	1,6	220 16 00			
HYDROGEN	1/16"	1,6	A-L	220 58 00		• The HP seal lens Réf.: 920 04 00A is delivered with the adaptor	1000 14500	1/8"	3,2		3/8" 24	920 52 00
OTHER GASES	1/16"	1,6	A-L	220 59 00			1000 - 2000 14500 - 2900	1/16"	1,6		3/8" 24	220 52 00

In view of possible technological advances in our production methods, the products described in this manual are liable to be modified without prior notice.



TOP INDUSTRIE
High Pressure Engineering

80 rue Marinoni 77013 VAUX LE PENIL CEDEX FRANCE

T : +33 (0) 1 64 10 45 50 F : +33 (0) 1 64 37 62 08

info@top-industrie.fr

www.top-industrie.com

B3A 0111